
TECHNICAL DATA

STABILIZERS/ RECYCLERS

RS 460, RS 500





Dimensions in mm

	A	B	H	H1	K	L
RS 460	6073	2872	3100	3885	510	9579
RS 500	6073	2530	3100	3885	510	9579

Shipping dimensions in m3

RS 460	85,284
RS 500	75,128

I. Soil stabilisation with cement and lime in sand and gravel				
Layer thickness	cm	20	30	50
Output	m² / day	14.000-17.000	9.000-14.500	6.500-10.000

II. Improvment with lime in mixed soils				
Layer thickness	cm	20	30	50
Output	m² / day	15.000-20.000	10.000-15.000	9.000-13.000

III. Pulverization of silt and clay				
Layer thickness	cm	20	30	50
Output	m² / day	7.000-11.000	6.000-9.000	4.500-8.000

IV. Mix in place recycling of asphalt roads **Normal total cutting depth 35 cm**				
Asphalt thickness	cm	5	10	15
Output	m² / day	7.000-9.000	5.500-7.580	3.000-5.000

Production rates can vary depending on materials and application type.

Technical Data		BOMAG RS 460	BOMAG RS 500
Weights			
Operating weight CECE	kg	24.150	24.900
Axle load, front CECE	kg	16.000	16.030
Axle load, rear CECE	kg	8.150	8.870
Max. weight	kg	27.300	31.000
Driving Characteristics			
Speed (1)	km/h	0- 3,0	0- 3,0
Speed (2)	km/h	0- 12,0	0- 12,0
Max. gradeability (dep. on soil con.)	%	40	40
Drive			
Engine manufacturer		Merc.-Benz	Merc.-Benz
Engine type		OM 460 LA	OM 460 LA
Emission stage		Stage IIIa / TIER3	Stage IIIa / TIER3
Cooling		Liquid	Liquid
Number of cylinders		6	6
Performance ISO 9249	kW	335,0	375,0
Performance SAE J 1995	hp	450,0	503,0
Speed	min-1	1.800	1.800
Electric equipment	V	24	24
Drive system		hydrost.	hydrost.
Driven wheels		all wheel	AWD 4x4
Tyres			
Tyre size, front		24.5-32 24PR	24.5-32 24PR
Tyre size, rear		23.1-26 20PR	23.1-26 20PR
Brakes			
Service brake		hydrost.	hydrost.
Parking brake		multi disc	multi disc
Steering			
Steering system		Art. + rear	Art. + rear
Steering method		hydraulic	hydraulic
Rotor			
Rotor width	mm	2.440	2.250
Rotor diameter, outer	mm	1.224	1.224
Rotor speed	min-1	104- 180	100- 180
Rotor oscillation angle +/-	grad	8	8
Sense of rotation		up-cut	up-cut
Max. cutting depth	mm	500	500
Number of cutting teeth		160	160
Height of cutting teeth	mm	290	240
Capacities			
Fuel	l	875,0	875,0
Water	l	850,0	850,0

Technical modifications reserved. Machines may be shown with options.

Standard Equipment

- ☑ Hydrostatic drive / all wheel
- ☑ Anti Slip Control (ASC) (RS460)
- ☑ Hydr./ mech. rotor drive with autom. power control
- ☑ Rotor laterally slidable (RS500)
- ☑ Hydr. adjustable rotor inclination, automatic
- ☑ BOMAG FLEXMIX Technology (RS500)
- ☑ Universal rotor with exchange holder BMS15
- ☑ Hydr. tailgate with floating position+Load application function
- ☑ Hydrostatic articulated steering
- ☑ Hydrostatic rear axle steering
- ☑ 4 Steering modes
- ☑ Height adjustable ROPS cab
  - Transport/working position
  - slewable/slidable multi-function work place
  - heating
  - Air condition
  - Radio
- ☑ Working lights (LED)
- ☑ Rotary beacon
- ☑ Camera system Plus
- ☑ 4x Emergency STOP
- ☑ Air compressor + Connecting port for compressed air tools
- ☑ Lockable stowage compartments
- ☑ Central lubrication system (RS500)
- ☑ Rotary unit for rotor forward/reverse
- ☑ Pneumatic hammer for changing cutting tools
- ☑ compressed air system + Compressed air set

Optional Equipment

- ☐ Water metering system (900l + 1600l)
- ☐ Water prefilter
- ☐ Emulsion metering system 900l/min.
- ☐ Emulsion pre-filter for water system
- ☐ Dosing bar for cement suspension
- ☐ Printer for metering computer
- ☐ Quick-change holder 20mm(BMS15)
- ☐ High pressure cleaner
- ☐ Central lubrication system (RS460)
- ☐ Tool kit
- ☐ Quick refuelling system
- ☐ BOMAG TELEMATIC POWER
- ☐ Special painting
- ☐ Widening of Track, front (RS500)
  Overall width: 2.800mm
- ☐ Vibratory plate (RS460)

BOMAG
Hellerwald
D-56154 Boppard
P.O. Box 5162
Tel. (0)6742 - 1000
Fax (0)6742 - 3090

BOMAG
FAYAT GROUP